



1. Identification of Substance & Company

Product

Product name PH CRTG Solvent Black SBK1035

HSNO approval HSR002662

Approval description Surface Coatings and Colourants (Flammable) Group Standard 2017

UN number 1210 DG class 3

Proper Shipping Name PRINTING INK

Packaging group II
Hazchem code 3YE
Uses Printing Ink

Company Details

Company MITech Limited
Address 60 Cawley Street
PO Box 394962
Ellerslie 1547

Ellerslie 1547 Auckland New Zealand +64 9 915 5555 askmi@mitech.co.nz

Telephone+64 9 915 5555Emailaskmi@mitech.co.nWebsitewww.mitech.co.nz

Emergency Telephone Number: 0800-764 766

2. Hazard Identification

Approval

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2017). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Minimum Degrees of Hazard) Notice 2017.

Classes Hazard Statements

3.1B
H225 - Highly flammable liquid and vapour.
6.1E (oral)
H303 - May be harmful if swallowed
6.3B
H316 - Causes mild skin irritation.
6.4A
H319 - Causes serious eye irritation.
6.9B (narcotic)
H336 - May cause drowsiness or dizziness.

SYMBOLS

DANGER





Other Classifications

There are no other classifications that are known to apply.

Precautionary Statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe vapours.
- P264 Wash hands thoroughly after handling.

Page 1 of 7 June 2019



Safety Data Sheet

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/eye protection.

P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.

P332+P313 - If skin irritation occurs: Get medical advice/ attention.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention. P308+P313 - IF exposed or concerned: Get medical advice/ attention.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

3. Composition / Information on Ingredients

| Component | CAS/ Identification | Conc (%) |
|------------|---------------------|----------|
| Ethanol | 64-17-5 | 60-70% |
| n-Propanol | 71-23-8 | 20-30% |
| Acetone | 67-64-1 | 1-5% |
| n-Butanol | 71-36-3 | 1-5% |

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been harmed or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service). IF exposed or concerned: Get medical advice/ attention.

Recommended first aid

Ready access to running water is required. Accessible eyewash is required.

facilities

Exposure

Swallowed

Do NOT induce vomiting. Give a glass of water to drink. If medical advice is needed,

have product container or label at hand. Call a POISON CENTER or doctor/physician if

you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Apply continuous irrigation with water for at least 15 minutes

holding eyelids apart. If eye irritation persists: Get medical advice.

Skin contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: get medical

advice/attention. Take off contaminated clothing and wash before re-use.

Inhaled IF INHALED: Remove to fresh air and keep at rest in a position comfortable for

breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Advice to Doctor

Treat symptomatically

5. Firefighting Measures

Fire and explosion hazards: Vapours may form an explosive mixture in air which can be ignited by many sources such

as pilot lights, open flames, electrical motors, switches and static electricity.

Suitable extinguishing Carbon dioxide, extinguishing powder, foam.

substances:

Unsuitable extinguishing

substances:

Unknown.

Products of combustion:

Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.

May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying

spaces, forming potentially explosive mixtures.

Protective equipment: Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat

and eye protection.

Hazchem code: 3YE



Safety Data Sheet

6. Accidental Release Measures

Containment If greater than 1000L is stored, secondary containment and emergency plans to manage

any potential spills must be in place. In all cases design storage to prevent discharge to

storm water.

Emergency procedures In the event of spillage alert the fire brigade to location and give brief description of

hazard. Stop the source of the leak, if safe to do so. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust. Prevent by whatever means possible any spillage from entering drains, sewers,

or water courses. (If this occurs contact your regional council immediately).

clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or

waterways has occurred advise local emergency services.

Disposal Mop up and collect recoverable material into labelled containers for recycling or salvage.

Recycle containers wherever possible. This material may be suitable for approved

landfill. Dispose of only in accord with all regulations.

Precautions Wear protective equipment to prevent skin and eye contamination and the inhalation of

vapours. Work up wind or increase ventilation.

7. Storage & Handling

Storage Avoid storage of harmful substances with food. Store out of reach of children.

Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in Section 10. Location compliance certificates must be available if storing >100L

(containers >5L), 250L (containers ≤5L), 50L (in use). Containers (and outer packaging)

must bear the prescribed labelling, including the Hazchem code, UN number,

flammability warning and name of contents.

Handling Keep exposure to a minimum, and minimise the quantities kept in work areas. See

section 8 with regard to personal protective equipment requirements. Avoid skin and eye

contact and inhalation of vapour, mist or aerosols.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace Ingredient WES-TWA* WES-STEL Exposure Stds Ethanol 1000ppm, 1880mg/m³ data unavailable

n-Propanol 200ppm, 492mg/m³ 250ppm, 614mg/m³
Acetone 500ppm, 1185mg/m³ 1000ppm, 2375 mg/m³
n-Butanol Ceiling 50 ppm, 150 mg/m³ data unavailable

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



Avoid contact with eyes. Use safety glasses and or chemical splash goggles if splashes are possible. Select eye protection in accordance with AS/NZS 1337.

Skin

If discomfort is felt (e.g., if pre-existing conditions exist, such as dermatitis, cuts or sensitive skin), gloves may be helpful. If you suffer from dermatitis type skin conditions, use gloves. Butyl rubber gloves are recommended. Protective gloves or suitably resistant material must comply with AS 2161. Replace frequently. Gloves should be checked for tears or holes before use.

Page 3 of 7 June 2019

Technology Group

PH CRTG Solvent Black SBK1035

Safety Data Sheet

Respiratory

A respirator when airborne concentrations approach the WES (section 8). Respirators must have filters appropriate to the duty and comply with AS/NZS1716 and selected, used and maintained in accordance with AS/NS 1715. Use a respirator with an organic vapour cartridge. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order. Fit testing and clear guidelines and training for use and maintenance of PPE are necessary.

WES Additional Information

Not applicable

9. **Physical & Chemical Properties**

Appearance liquid Odour solvent рΗ no data Vapour pressure no data **Viscosity** no data **Boiling point** no data Volatile materials no data Freezing / melting point no data

partly soluble in water Solubility

Specific gravity / density not specified Flash point 12°C **Danger of explosion** no data **Auto-ignition temperature** no data Upper & lower flammable limits no data Corrosiveness non corrosive

10. Stability & Reactivity

Stability Stable

Conditions to be avoided Flammable substance. Keep away from sources of ignition at all times. Containers should

be kept closed in order to avoid contamination.

Incompatible groups Strong oxidising agents

None known

Oxides of carbon

Substance Specific Incompatibility

Hazardous decomposition

products

Hazardous reactions None known

11. **Toxicological Information**

Summary

If SWALLOWED: if large quantities are swallowed: symptoms include nausea and vomiting. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

IF IN EYES: May cause severe eye irritation.

IF ON SKIN: repeated or prolonged exposure may cause skin irritation and dermatitis (non-allergic), due to degreasing properties of the product.

IF INHALED: May high concentrations may cause irritation of the respiratory tract. vapours may cause dizziness and drowsiness. High concentrations may cause central nervous system depression, headaches, dizziness, tiredness and incoordination and in extreme cases loss of consciousness.

| Supporting Data | | |
|-----------------|---------|--|
| Acute | Oral | Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (oral, rat) for the mixture is between 2000 and 5000mg/kg. Data considered includes: Ethanol >5000mg/kg, n-propanol 1970mg/kg (rat), Acetone 3000 mg/kg (mouse), n-butanol 790 mg/kg (rat). |
| | Dermal | Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (dermal, rat) for the mixture is $>$ 5000 mg/kg. Data considered includes: Ethanol $>$ 5000mg/kg, n-propanol 4049mg/kg (rabbit), Acetone data unavailable, n-butanol 3400 mg/kg (rabbit). |
| | Inhaled | Using LC ₅₀ 's for ingredients, the calculated LC ₅₀ (inhalation, rat) for the mixture is $>5mg/L$. Data considered includes: n-butanol 24.3 mg/l (rat). |
| | Eye | The mixture is considered to be an eye irritant, because some of the ingredients present are considered eye irritants in more concentrated form. |
| | Skin | The mixture is considered to be a skin irritant, because some of the ingredients present are considered skin irritants in more concentrated form. |

Page 4 of 7 June 2019



Safety Data Sheet

Chronic Sensitisation

Mutagenicity
Carcinogenicity
Reproductive /

No ingredient present at concentrations > 0.1% is considered a sensitizer. No ingredient present at concentrations > 0.1% is considered a mutagen. No ingredient present at concentrations > 0.1% is considered a carcinogen. No ingredient present at concentrations > 0.1% is considered a reproductive or

Developmental Systemic

developmental toxicant or have any effects on or via lactation. Inhalation of vapour may cause dizziness and drowsiness.

None known.

Aggravation of existing conditions

12. Ecological Data

Summary

This mixture is not considered ecotoxic. In all cases prevent run-off to drains, sewers and waterways.

Supporting Data

Aquatic Using EC₅₀'s for ingredients, the estimated EC₅₀ for the mixture is > 100 mg/L.

Bioaccumulation No data
Degradability No data

Soil No evidence of soil toxicity.

Terrestrial vertebrateThis mixture is not considered ecotoxic to terrestrial vertebrates. See acute toxicity.

Terrestrial invertebrate No evidence of toxicity towards terrestrial invertebrates.

Biocidal no data

13. Disposal Considerations

Restrictions There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

Disposal method Disposal of this product must comply with the Hazardous Substances (Disposal) Notice

2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

Contaminated packaging Disposal of contaminated packaging must comply with the Hazardous Substances

(Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible

Product Name: PH CRTG Solvent Black SBK1035

reuse or recycle packaging.

14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a hazardous substance for

transport.

UN number: 1210 **Proper shipping name:** PRINTING INK

Class(es) 3 Packing group:

Precautions: Flammable liquid Hazchem code: 3YE

IMDG

UN number: 1210 **Proper shipping name:** PRINTING INK

Class(es) 3 Packing group:

Precautions: Flammable liquid **EmS** F-E, S-D

IATA

UN number: 1210 **Proper shipping name:** PRINTING INK

Class(es)3Packing group:IIPrecautions:Flammable liquidERG Code3L

ComitechTechnology Group

PH CRTG Solvent Black SBK1035

Safety Data Sheet

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002662, Surface Coatings and Colourants (Flammable) Group Standard 2017.

All ingredients appear on the NZIoC.

Specific Workplace Controls (as per HSNO approval referenced to Controls Matrix)

Key workplace requirements are:

SDS To be available within 10 minutes in workplaces storing any quantity.

Inventory An inventory of all hazardous substances must be prepared and maintained.

Packaging All hazardous substances should be appropriately packaged including substances

that have been decanted, transferred or manufactured for own use or have been

supplied

Labelling Must comply with the Hazardous Substances (Labelling) Notice 2017.

Emergency plan Required if > 1000L is stored.

Certified handler Not required. Tracking Not required.

Bunding & secondary containment Required if > 1000L is stored. Signage Required if > 250L is stored.

Location compliance certificate Required if > 100L (containers >5L), 250L (containers $\le 5L$), 50L (in use) is stored. Flammable zone Must be established if > 100L (closed containers), 25L (decanting), 5L (open

occasionally), 1L (in use), stored in any one location is stored.

Fire extinguisher If > 250L present.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code Approval HSR002662, Surface Coatings and Colourants (Flammable) Group Standard

2017 Controls, EPA. www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical

agent to which a worker may be exposed at any time.

EC50 Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

EPA Environmental Protection Authority (New Zealand)

HAZCHEM Code Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

HSNO Hazardous Substances and New Organisms (Act and Regulations)

International Agency for Research on Cancer

LEL Lower Explosive Limit

LD₅₀ Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population

(usually rats)

NZIoC New Zealand Inventory of Chemicals

MSDS (SDS) Material Safety Data Sheet (or Safety Data Sheet)

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

TWA Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UEL Upper Explosive Limit
UN Number United Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring

using procedures that gather air samples in the worker's breathing zone.

Page 6 of 7 June 2019



Safety Data Sheet

References

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: EU ECHA, ingredients SDS's, ChemIDplus

Review

Date Reason for review

June 2019 Not applicable – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.



Page 7 of 7 June 2019